

NETZSCH

Proven Excellence.



Accelerating Rate Calorimetry

Advanced Solution for Chemical Process Safety,
Energetic Material, and Battery Development

Analyzing & Testing

Accelerating Rate Calorimetry



ARC® 244

ADIABATIC WORKING PRINCIPLE

A Key Tool to Understand Thermal Runaway

Accelerating rate calorimetry has been the cornerstone of chemical process safety for the last 30 years. These cases require measuring both the amount of heat released (thermodynamics) and the rate at which it is released (kinetics). This can cause significant increase in sample pressure. The combination of temperature and pressure rise can lead to an explosion. Therefore, adiabatic calorimeters are generally designed to be much more robust than many other types of calorimeters.

When looking at a thermal runaway as a part of a chemical process in a reactor, the reaction produces heat which increases the temperature of the reaction mixture and further increases the rate of reaction. There can come a point when the rate of heat release from the reaction exceeds the rate at which the heat can be lost to the surrounding environment – the point at which thermal runaway starts.

Obviously, the worst case is when there is little or no ability for the heat to be lost to the environment. Any heat, even small amounts of heat, cause the temperature to rise and accelerates the reaction producing even more heat. This is the adiabatic condition and it is this precise condition that adiabatic calorimeters can safely measure in the small scale. It is this same condition that can be found inside large processing vessels as well as inside a Li-ion pack running inside a laptop computer.


NETZSCH – a New Level of Adiabatic Calorimetry

The adiabatic principle is realized in instruments that work according to the accelerating rate calorimetry. The instruments described herein are the best in their class. With the patented *VariPhi*[®] system, not only can adiabatic test be done more accurately but it also opens up new areas of calorimetry not possible with the original ARC[®] units. The systems have been enhanced to do more and answer more questions.



ARC[®] 305

Method



Adiabatic System: No heat in – no heat out


The energy release from chemical reactions (decomposition, etc.) is a point of focus in chemical research and other industries. When energy is generated by a thermally induced chemical reaction and the heat transfer to the outside is smaller than the generated amount, runaway reactions can occur. In the worst case, this can cause catastrophic events (explosions).

Adiabatic calorimeters are ideal tools for analyzing such scenarios as they simulate the worst case scenario with no heat exchange with the surroundings. The behavior in real large scale chemical reactors can therefore be simulated.

For decades accelerating rate calorimetry has been widely used by researchers in this field, offering the capability to measure temperatures, enthalpy changes and pressure changes quantitatively.

Technique

A sample (several grams) is placed in a spherical vessel. The vessel is surrounded by a sophisticated heating system. Depending on the working mode, the surroundings of the vessel are controlled to the same temperature as the sample. If there is no temperature difference between the heaters and the sample, then all the heat generated by the sample stays within the sample. This is the adiabatic condition.



Schematic of the ARC® 305 Calorimeter Assembly
TC = Thermocouple


Understanding Accelerating Rate Calorimetry

Heat-Wait-Search mode (HWS) represents a careful approach to the reaction temperature:

- Heating the sample material to a certain temperature → Heat
- Isothermal stabilization → Wait
- Change to the adiabatic mode → Search (as soon the self-heating rate of the sample extends a customer-defined threshold (usually 0.02 K/min))

Measurement Results

A thermal runaway reaction is usually investigated with the Heat-Wait-Search mode (HWS). The temperature of reaction as well as the temperature and pressure increase are measured. Additionally, the temperature and pressure increase rates can be determined. These are important values in order to characterize the worst case scenario of a substance.



Thermal runaway reaction of a 20% solution of di-tert. butyl peroxide (DTBP) in toluene.

*The Original DOW Design
for Basic ARC[®] Testing*

Accelerating Rate Calorimetry ARC[®] 244

The cost-effective ARC[®] 244 is designed to safely measure the amount and rate of heat release associated with the processing or storage of chemicals within a container volume between 1.0 ml and 8.5 ml. This is the calorimeter which uses the same design as the first ARC[®] system developed by DOW for those customers interested in keeping the same platform.

Key Features

- Operation modes:
 - Heat-Wait-Search (primary mode of operation)
 - Iso-Fixed technique
 - Iso-Track technique
 - Ramp mode for fast screening of unknown samples
- With *VariPhi*[®]
 - Heat-Wait-Search, with $\Phi = 1$
 - Constant power
 - Constant heating rate
 - Fire exposure
 - True isothermal mode



ARC[®] 244



ARC® 244 Calorimeter Assembly

Operating Modes

- Heat-Wait-Search test for thermal runaway reactions
- Iso-Fixed/Iso-Track for studying storage conditions/auto-catalytic reactions (iso-aging technique)
- Ramp mode for fast screening of unknown samples

Optionally with *VariPhi*®

Scanning and isothermal modes allow detection of exothermic and endothermic effects; similar to the DSC method

Features	Advantages	Benefits
Motorized headlift	operator not required to lift calorimeter lid and can set working height based on personal preference	easy for all operators to use safely and quickly
Over-temperature protection	one safety thermocouple monitors calorimeter temperatures and shuts down the system independent of the software	protects heaters and other instrument parts from runaways
Tube heater	heats the pressure transfer tube to the same temperature as the sample	prevents refluxing and sample loss which can cause great underestimation of heats of reaction and temperature and pressure rates
Iso-fixed mode	allows the user to run isothermal aging tests for many days with minimized drift	more accurate and reliable data
Automated anneal, temp.	the user can quickly set-up the anneal-adjustment-drift test sequence. The software will automatically go from one test to the next	no operator intervention necessary, improved efficiency

*Advanced Technology
for Specialized Testing*

Accelerating Rate Calorimetry

ARC[®] 305

The advanced ARC[®] 305 helps engineers and scientists identify potential hazards and tackle key elements of process optimization and thermal stability. As a highly versatile, miniature chemical reactor, sample can be stirred, material injected, and it can be used for vent studies. The ARC[®] 305 has been designed to use the traditional 10 ml ARC spherical vessel but can also use the larger 130 ml vessel for low Phi or vent testing.

Key Features

- RT to 500°C
- Operation modes:
 - Heat-Wait-Search (primary mode of operation)
 - Iso-Fixed technique
 - Iso-Track technique
 - Ramp mode for fast screening of unknown samples
 - High tracking rate
- With *VariPhi*[®]
 - Heat-Wait-Search, with $\Phi = 1$
 - Constant power
 - Constant heating rate
 - Fire exposure mode
 - True isothermal mode



ARC[®] 305



Operating Modes

- Heat-Wait-Search test for thermal runaway reactions of chemicals
- Iso-Fixed/Iso-Track for studying storage/conditions/auto-catalytic reactions (iso-aging technique)
- Ramp mode for screening unknown samples

Optionally with *VariPhi*[®]

- Scanning and isothermal modes allow detection of exothermic and endothermic effects; similar to the DSC method
- In-situ battery cycling using isothermal calorimeter mode
- Low PHI-test with compensation

Features*	Advantages	Benefits
Temperature tracking rate up to 200 K/min	fast reactions can be tracked without the need to increase thermal inertia	more reliable data and wider application range
Machined gas-tight ceramic insulation	provides consistent insulation properties (i.e. density, geometry)	constant insulation properties provide for accurate test results, easy cleaning
True temperature calibration	with <i>VariPhi</i> [®] temperature measurements can be corrected to standards	more accurate onset temperature

* in addition to ARC[®] 244 features

The basis of the *VariPhi*[®] is an additional controlled variable DC heater. With this option, it is possible to define the thermal inertia in order to allow real-world thermal environment by compensating for heat lost from the sample to the vessel. By operating different modes such as isothermal or scanning, endothermic and exothermic transitions can be quantified and pressure data can be measured.

VariPhi[®]

A Patented Solution for Low Phi Operation and Reduced Testing Time

Theory

Sample containers absorb some of the energy from the reaction. How much heat is absorbed depends upon the mass and heat capacity of the sample container. The ratio between mass and specific heat capacity of the container and mass and specific heat capacity of the sample is what is known as thermal inertia.




Diagram of *VariPhi*[®]

Low Phi Tests

When the sample mass is large compared to the container mass, the thermal inertia approaches one. These tests are often called “low phi” tests. They are important because most industrial scale processing or storage conditions are low thermal inertia conditions. The mass of a large storage container is very small compared to the mass of the stored material. Since this is not always true, it is important to be able to run multiple tests at varying thermal inertia. The *VariPhi*[®] gets its name because the user can quickly and easily run low and high thermal inertia (“Phi”) tests in the same calorimeter using a small and inherently safer sample size.

Formula for thermal inertia (Φ-factor) according to ASTM E1981:

$$\Phi = \frac{(m_s \cdot C_{p,s} + m_c \cdot C_{p,c})}{m_s \cdot C_{p,s}} \quad \Phi = 1 + \frac{m_c \cdot C_{p,c}}{m_s \cdot C_{p,s}}$$

m_c = mass of the container
 $C_{p,c}$ = heat capacity of the container
 m_s = mass of the sample
 $C_{p,s}$ = heat capacity of the sample

Standard Modes such as Heat-Wait-Search, Iso-Fixed or Iso-Track

- Compensation for heat lost to the sample container during test
- Thermal inertia or Phi (Φ) factor can be defined
- Low Phi testing with small samples

Scanning Mode


- Reduces test time by 75% or more without loss of sensitivity
- Endothermic transition can be accurately measured

Fire-Exposure Mode

Simulation of additional heat to the sample during external fire scenario.

Isothermal Mode

True isothermal calorimeter mode is possible on chemical samples.



Testing Vessels for the Accelerating Rate Calorimeters

A broad variety of testing vessels are available to meet different test requirements. Tube-type vessels are available for running energetic materials and for use with solids and pastes in the *VariPhi*[®] mode. For battery testing, specific holders are designed for common commercial sizes. Custom vessels can also be designed.

Materials

- Spherical vessels with a wall thickness between 0.4 mm and 0.9 mm are made of Hastelloy, stainless steel and titanium
- Tube-type vessels with a wall thickness between 0.4 mm and 0.9 mm are made of stainless steel and titanium

Volume

- 1 ml to 130 ml for spherical vessels
- 1 ml to 8.5 ml for tube-type vessels



	ARC® 244	ARC® 305
Temperature range	RT to 500°C	RT to 500°C
Pressure range (Standard)	0 bar to 150 bar	0 bar to 150 bar
Lift mechanism	motorized	motorized
Typical sample volume*	0.5 ml to 8.5 ml	0.5 ml to 130 ml
Max. tracking rate	20 K/min	200 K/min
Temperature reproducibility	0.1 K	0.1 K
VariPhi®	Optional	Optional
Operating mode	<ul style="list-style-type: none"> ■ Heat-Wait-Search ■ Constant heating rate ■ Isothermal 	<ul style="list-style-type: none"> ■ Heat-Wait-Search ■ Constant heating rate ■ Isothermal
Stirring	Optional	Optional
Injection	Optional	Optional
Venting	Optional	Optional
Low Φ factor	Yes, pressure-dependent**	Yes, pressure-dependent**
Kinetics software	Optional	Optional
Applications	<ul style="list-style-type: none"> ■ Process Safety ■ Comparison to legacy data 	<ul style="list-style-type: none"> ■ Process Safety ■ Energetic Materials


* Sample volumes shown are typical and not limits. The choice of sample vessels can influence test results. See product manual or spare parts list for more details.

** Dependent on sample pressure built-up


Technical Specifications

Configurable Options to Match Testing Needs

ARC[®]244 options



ARC[®]305 options



Selecting the Best Calorimeter for Your Applications


Intelligent Software Solutions

Measurement Task

The measurement software for the ARC® systems offers easy setup of a measurement, selection of the measurement mode and follow-up of the test progress. All raw data signals are accessible on the screen, switches can be set with one mouse click and simple plots of the running measurements can be generated. The software stores data in binary and ASCII formats, making it easy to load results into other software packages for advanced analysis.




- Software automatically customizes itself to the instrument and application
- Intuitive windows set-up of testing methods with input checks to reduce typos
- Methods can be saved and recalled for later use
- Online help, comprehensive and easy to understand, available throughout the software
- Data is automatically saved to hard-drive throughout the run
- Intelligent firmware monitors the status and health of key operating sensors and active components
- Safety integrated with hardware and firmware controls
- Seamless integration of data files to *Proteus*®
- Analysis, NETZSCH Advanced Software Tools



Screenshot of the *Proteus*® evaluation software

Evaluation Software

Analysis of the measurements is done using the well-known *Proteus*® Thermal Analysis software. Presentation of measurement results such as various temperatures, heat generation rates or the pressure development can be done in one plot. Direct evaluation of decomposition enthalpies and standard kinetic analysis is possible.



Comparison of measured and calculated data for different Φ -factors

Advanced Thermokinetic and Thermal Simulation


Most decomposition reactions cannot be explained by simple kinetic approaches. In such cases, the nature of a reaction is based on various steps (consecutive, parallel or competitive reactions). Multiple step reactions with more than 15 different reaction types can be used in NETZSCH *Kinetics Neo* for the analysis of the results. This is the ideal tool for understanding the real chemistry and kinetics behind a reaction.

Typical Applications


Accelerating Rate Calorimetry by NETZSCH can be used for the Thermal Analysis of solid or liquid chemicals or for gas/liquid, liquid/liquid, gas/solid, and liquid/solid mixtures. They can also be used for process simulation of batch and semibatch reactions, fire exposures, emergency relief venting, and physical properties measurement.

Energetic Materials

Ammonium nitrate is a base material for various applications, such as fertilizers. Measured here are solid-state phase transitions and melting (at 166°C) as well as the decomposition behavior, starting at 221°C. Such tests are crucial for safety studies on such highly energetic materials.



Analysis of the phase changes and decomposition behavior of ammonium nitrate using the *VariPhi*® option




Autocatalytic behavior of 3 g 3-methyl-4-nitrophenol at 180°C (isothermal)

Autocatalytic Behavior


3-methyl-4-nitrophenol displays autocatalytic behavior when heated to decomposition temperatures. This may be studied using the Iso-Track or Iso-Fixed feature of the calorimeter control software. Using the *VariPhi*® option allows measurement of the sample under true isothermal conditions. The plot shows the autocatalytic nature of the material where the sample heat flux initially increases and then decreases due to consumption of reactant. The total heat release during decomposition is obtained by integration of the heat flux signal.

Vented Tests

All ARC[®]s may be operated in vented or open vessel mode. For vented tests, a computer-controlled valve is opened which allows material to flow to a 500 ml drop-out pot. If the pressure in the reaction vessel ceases to rise and the sample temperature remains flat or is tempered, then the reaction may be classified as a vapor system. The pressure in the reaction vessel may continue to rise, but at a reduced rate because of the increase in the head space of the reaction vessel. At the end of the test, the contents of the drop-out pot are available for analysis.



Vented tests showing increasing tempering as the vent set pressure is reduced



Temperature plotted versus Time-to-Maximum-Rate (logarithmic scaling) for a measurement performed with 5.74 g of DTBP in toluene in a titanium sample vessel (Φ -factor = 1.489)

If the substance/mixture is stored in a vessel which exhibits heat loss in the order of $\Phi = 1.489$, then the maximum self-heating rate will be reached after 82 hours. However, if there is no heat loss during storage ($\Phi = 1$), the maximum self-heating rate will be already achieved after 55 hours.

Time-to-Maximum-Rate (TMR)

In order to identify potential hazards of chemicals during processing and storage often the Time-to-Maximum-Rate (TMR) is measured under adiabatic conditions. This information is used for predicting the temperatures for safe storage of chemicals. TMR is the time between the start of a thermal runaway reaction and the maximum reaction rate (maximum self-heating rate). In case a chemical reactor faces the hazardous event of a runaway reaction, the maximum reaction rate is equivalent to an explosion. As the experimentally observed TMR value using the ARC is influenced by the Φ -factor of the reaction vessel usually a correction to $\Phi = 1$ is done which in fact predicts the worst case scenario.



Expertise in Service

Our Expertise – Service

All over the world, the name NETZSCH stands for comprehensive support and expert, reliable service, both before and after sale. Our qualified personnel from the technical service and application departments are always available for consultation. In special training programs tailored for you and your employees, you will learn to tap the full potential of your instrument. Choose your preferred training method: Online, on-site or at our NETZSCH training center.

To maintain and protect your investment, you will be accompanied by our experienced service team over the entire life span of your instrument.

Our Expertise – Applications Laboratories

The NETZSCH Thermal Analysis applications laboratories are a proficient partner for nearly any Thermal Analysis issue. Our involvement in your projects begins with proper sample preparation and continues through meticulous examination and interpretation of the measurement results. Our diverse methods and over 30 different state-of-the-art measuring stations will provide ready-made solutions for all your thermal needs.

Within the realm of thermal analysis and the measurement of thermophysical properties, we offer you a comprehensive line of the most diverse analysis techniques for materials characterization.

Measurements can be carried out on samples of the most varied of geometries and configurations. You will receive high-precision measurement results and valuable interpretations from us in the shortest possible time. This will enable you to precisely characterize new materials and components before actual deployment, minimize risks of failure, and gain decisive advantages over your competitors.

TECHNICAL SERVICE



Maintenance and Repair



Software Updates



Exchange Service



IQ/OQ Documents



Calibration Service



Spare Part Assistance



Moving Service

TRAINING



Basic Seminars



NETZSCH Online Academy



Comprehensive Instrument and Method Training

LABORATORY



Application Service and Contract Testing

The owner-managed NETZSCH Group is a leading global technology company specializing in mechanical, plant and instrument engineering.

Under the management of Erich NETZSCH B.V. & Co. Holding KG, the company consists of the three business units Analyzing & Testing, Grinding & Dispersing and Pumps & Systems, which are geared towards specific industries and products. A worldwide sales and service network has guaranteed customer proximity and competent service since 1873.

When it comes to Thermal Analysis, Calorimetry (adiabatic & reaction), the determination of Thermophysical Properties, Rheology and Fire Testing, NETZSCH has it covered. Our 60 years of applications experience, broad state-of-the-art product line and comprehensive service offerings ensure that our solutions will not only meet your every requirement but also exceed your every expectation.

Proven Excellence. ■

NETZSCH-Gerätebau GmbH
Wittelsbacherstraße 42
95100 Selb, Germany
Tel.: +49 9287 881-0
Fax: +49 9287 881-505
at@netsch.com
<https://analyzing-testing.netsch.com>



NETZSCH®

www.netsch.com